



# COMBUSTIBLE & OXYGEN INDICATORS

Gas Detection For Life

P-200 Series



## Features

- Fast Response
- Light Weight
- Rugged Construction
- Simple to Operate
- Economical
- Field Proven Dependability

## Industry Applications

- Industrial Applications
- Land Fills
- Utilities
- Public Works

The P-200 series gas detectors are rugged, lightweight, hand held portables for detecting combustible gases/vapors and monitoring atmospheric oxygen content. Engineered to serve the demanding field requirements of industrial, public works, utilities, and landfills, these instruments share many common features and offer the user distinct advantages in terms of economy, dependability, maintainability and ease of operation. Built to withstand rough field environments, all Series P-200 instruments are constructed with rugged cast aluminum housings, and incorporate highly reliable electrical design characteristics. All active and passive components are mounted on easily accessible printed circuit boards. In operation, all P-200 instruments are not only easy to use, sharing common functional characteristics, but they are extraordinarily fast in providing accurate readings. For combustible indicators, the response time is about 4 seconds, and for oxygen indicators an accurate reading is attained within 6 seconds.

By maximizing the use of common components and operating characteristics, RKI offers not only high quality field instruments, but has greatly simplified and expedited other very important considerations, such as field service, personnel training and accessory interchangeability. The commonality of components can save valuable time when field service becomes necessary. Fundamental operating features are easy to understand and all components are very accessible for checkout, replacement or repair.

# P-200 Series

## Specifications:

Model	GP-204 Combustible Indicator	NP-204 Natural Gas Detector	XP-204 Oxygen Deficiency Indicator	XP-204A Oxygen, Amplified Dual Range Indicator
<b>Part Number</b>	72-0001RK*	72-0004RK*	72-0050RK	72-0052RK
<b>Range</b>	0 - 100% LEL	0 - 100% LEL 0 - 100% Volume	0 - 25% Volume	0 - 25% Volume 0 - 5% Volume
<b>Calibration</b>	Methane		Oxygen	
<b>Detection Method</b>	Catalytic Combustion	Catalytic Combustion (LEL) Thermal Conductivity (Vol)	Electrochemical Sensor	
<b>Response Time</b>	4 seconds		6 seconds	
<b>Sampling Method</b>	Hand aspirated			
<b>Batteries</b>	2 "D" size (Alkaline or Nicad)		9 volt transistor type	
<b>Operating Hours</b>	6 (Alkaline) 4 (Ni-Cads)		30	
<b>Operating Temperature</b>	0 - 120 F (-15 to +50 C)		10 - 110 F (-12 to +45 C)	
<b>Meter Light</b>	Standard		N / A	
<b>Size</b>	6.5" x 5.3" x 4"			
<b>Weight</b>	5 lbs		3 lbs	

\* NOTE: Part numbers are for alkaline versions. Add a -01 suffix to the part number for Ni-Cad versions.

Specifications subject to change without notice.

Made in the USA

## RKI Instruments, Inc.



33248 Central Ave.  
Union City, CA 94587  
Toll Free: (800)754-5165  
Phone: (510)441-5656  
Fax: (510)441-5650  
mail4rki@rkiinstruments.com  
[www.rkiinstruments.com](http://www.rkiinstruments.com)

## Authorized Distributor: